

BERNAL[®]

TORANTRIEBE

Gamma 60**Artnumber: B252.15****Price excl. VAT: Prices on request****Fittings:**

Softrun: Reduced opening and closing speed to protect your garage door.,
 Emergency Release: Integrated emergency release (from in/outside depending on the door)., Security Lock: Extra strong gear brake as a locking mechanism in case of burglary attempts., Auto-Close: Automatic closing of your garage door after entry and exit., Steel Drive: Drive train with a long life due to a steel chain and a driving gear., Welcome Home: Integrated garage lighting with freely adjustable duration of lighting., Flexi-Fit: Universal fitting for use in swinging and sectional doors., Easy Mount: Simple installation using pre-mounted components., Secure: Safe radio system with fix code encryption., Remote-Control: 4-channel hand-held transmitter with 433.92 MHz., Warranty: The original warranty by BERNAL.

Design principle	garage door operator
Materials used	Plastics, steel
Weight (including accessories box & 3 m rail)	14 kg
Temperature range	-20 °C bis +40 °C
Suitable environment for use indoor / outdoor	Yes
Suitable environment for use outdoor	No
Motor type	24 V direct current geared motor
Tensile or compressive force	550N (Max. 600 N)
Motor power	110 W
Opening speed	12 cm/s
Reduced opening and closing speed to protect your garage door.	Yes
Mains connection	230 V alternating current / 50 Hz
Integrated emergency release (from in/outside depending on the door).	Yes (with Accessoires) / Yes
Stand-By consumption	~8W
Integrated lighting	1x12V/10W
Radio system	433.92 MHz
Radio encryption	Fix code
Maximum radio range (outdoors)	~ 40 m
Operating and programming concept	Pushbutton on the printed circuit board
Suitable for garages with maximum number of parking spaces	Max. 4
Suitable for garages with maximum openings (open and close) per day	Max. 8
Door type - Sectional door	Yes
Door type - swing gate	Yes
Suitable for door height up to (Swing gates)	2,4 m
Suitable for door height up to (Sectional door)	2,3 m
Suitable for doors with maximum weight up to:	60 kg
Suitable for doors with maximum width up to:	3,5 m
Suitable for doors with maximum door area up to:	6,5 m ²
Door size - Single door (metal / wood)	Yes / No
Door size - Double door (metal / wood)	No / No
Extra strong gear brake as a locking mechanism in case of burglary attempts.	Yes
Drive train with a long life due to a steel chain and a driving gear.	Yes
Automatic closing of your garage door after entry and exit.	Yes
Universal fitting for use in swinging and sectional doors.	Yes
Simple installation using pre-mounted components.	Yes
4-channel, 433.92 MHz hand-held transmitter.	Yes
The original warranty by BERNAL.	2 Years
Rail	M
Stand-By consumption	3m (2,47m)

Stand 2014-06-08

Technische Angaben und Abbildungen sind unverbindlich. Für Druckfehler und Irrtümer übernehmen wir keine Haftung.

BERNAL Torantriebe GmbH
 Industriepark Sandwiesen
 D-72793 Pfullingen

Telefon +49-(0)-7121-707-240
 Telefax +49-(0)-7121-707-225
 www.bernal.de